



# LAD 2420

## SPECIFICATIONS

### DESCRIPTION

#### MODEL - LAD 2420G

GVWR - 20,000 lbs.

Over All Length - approx. 33 ft. 6 in. (Approximate)

Over All Width - 102 in.

Empty Weight - 9,500 lbs.

### RUNNING GEAR

Axle - 10,000 lbs.

Brakes - Electric

Dual Tires - 8) ST235/80R16 Load Range (E) 80 psi

Wheels - 16" Silver Mod Dual Wheels

### FRAME

Main Frame - 10 in. I-beam

Cross Members - 3 in. Channel

Gooseneck Tongue - 10 in. I-beam

### LOWER DECK

Size - 24 ft. Long x 97 in. Wide

Material - 2 x 8 Treated kiln dried pine

### TOP DECK

Size - 33 ft 6 in. x 92 in.

Center Landing - 24 ft. Long x 92 in. Wide

Material - 2 x 8 Treated kiln dried pine

Cross Members - 2 x 2 x 3/16" Angle

### ELECTRICAL

Plug - 7 Way Molded Plug

Wiring - Enclosed in conduit w/ junction boxes  
- connections soldered & shrink wrapped

Lights - Standard LED package

### SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

### ACCESSORIES

Dual Jacks - 12K Side wind with drop legs

Tiedowns - E-Track on top and bottom deck

### FINISH

PPG Paint - Industrial urethane- Black, Orange, Yel, White

### ADDITIONAL OPTIONS

Dual Hydraulic Jacks - Electric over hydraulic

Bumper Pull Setup - 4 x 6 in. Rec Tube

Dual Side Platforms - 24 ft. Long x 6 ft. Wide

Single Side Platforms - 24 ft. Long x 6 ft. Wide

Seed Delivery - Vacuum System

