



LAD 2016G

SPECIFICATIONS

DESCRIPTION

MODEL - LAD 2016G

GVWR - 16,000 lbs.

Over All Length - appox. 29 ft. 6 in. (Approximate)

Over All Width - 102 in.

Empty Weight - 8,500 lbs.

RUNNING GEAR

Axle - 8,000 lbs.

Brakes - Electric

Single Tires - 4) ST215/75R17.5 Load Range (H)

Wheels - 17.5 x 6.75 8 Bolt White mod

FRAME

Main Frame - 10 in. I-beam

Cross Members - 3 in. Channel

Gooseneck Tongue - 10 in. I-beam

LOWER DECK

Size - 20 ft. Long x 97 in. Wide

Material - 2 x 8 Treated kiln dried pine

TOP DECK

Size - 29 ft 6 in. x 92 in.

Center Landing - 20 ft. Long x 92 in. Wide

Material - 2 x 8 Treated kiln dried pine

Cross Members - 2 x 2 x 3/16" Angle

ELECTRICAL

Plug - 7 RV Molded Plug

Wiring - Enclosed in conduit w/ junction boxes

- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

ACCESSORIES

Dual Jacks - 12K Side wind with drop legs

Tiedowns - E-Track on top and bottom deck

FINISH

PPG Paint - Industrial urethane- Black, White, Yellow, Or

ADDITIONAL OPTIONS

Dual Hydraulic Jacks - Electric over hydraulic

Bumper Pull Setup - 4 x 6 in. Rec Tube

Side Platforms - 20 ft. Long x 6 ft. Wide





