



LRGE 1007



SPECIFICATIONS

DESCRIPTION

MODEL - LRGE 1007

GAWR - 7,000 lbs.

Over All Length - approx. 114 in.

Over All Width - 102 in.

Reel Capacity - 4 ft. to 10 ft. in Diameter x 64 in. Wide

Empty Weight - 1,400 lbs.

RUNNING GEAR

Axle - 7,000 lbs.

Brakes - Electric

Tires - 235/80R16 LRE

Wheels - 16 x 6 Silver Mod

FRAME

Main Frame - 4 x 6 in. Rectangular tube

Gun Rack Shell - 4 x 4 in. Square tube

Gun Rack Support - 3 1/2 x 3 1/2 in. Square tube

Gun Rack - 3/4 in x 5 1/2 in. flat

A-Frame Tongue - 4 x 6 in. Rectangular tube

Light Boxes - 3 x 5 in. Rectanular tube

Fenders - 10 G. A. Formed steel

SPINDLE BAR

Material - 2 1/2 in Diam. CRR

ELECTRICAL

Plug - 7 RV molded plug

Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

ACCESSORIES

Jack - Single 8K top wind drop leg jack

Grounding Lug - 1/2 in. Round stainless

FINISH

PPG Paint - Industrial urethane- White, Black, Orange, Yel.

HYDRAULICS

Cylinders - 2 x 20 in. welded

Pump - Dual manual

- 95 cu. In.

Fluid - Dexron III / Mercon A.T.F.

