



LRS 0214

SPECIFICATIONS

DESCRIPTION

MODEL - LRS 0214

GVWR - 14,000 lbs.

Over All Length - appox. 26 ft.

Over All Width - 102 in.

Reel Capacity - 10 ft. x 60 in.

Empty Weight - 4,960 lbs.

RUNNING GEAR

Axle - 7,000 lbs.

Brakes - Electric
Tires - 235/80R16 LRE

Wheels - 16 x 6 8 Bolt Silver mod

FRAME

Main Frame - 6 in. Ibeam

Cross members - 6 in. Channel

Uprights - 2 x 3 in. Rectangular tube

Fenders - 12 in. Channel

Catwalk - 10 in. Channel

Bumper - 4 x 6 in. Rectangular tube

Tongue - 4 x 6 in. Rectangular tube

SPINDLE BAR

Material - 2 1/2 in Diam. CRR

ELECTRICAL

Plug - 7 RV molded plug

Wiring - Enclosed in conduit w/ junction boxes

- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

ACCESSORIES

Wheel Chocks - Rumber

Jack - Single 12K spring loaded drop leg

FINISH

PPG Paint - Industrial urethane- White, Black, Orange, Yel.

HYDRAULICS

Cylinders - 4 x 24 in.

Pump - 5 HP Honda motor

Valve - 1 Spool

Fluid - 303 Hydraulic fluid







