



1010R

## SPECIFICATIONS

DESCRIPTION
MODEL - LRG 1010R
GAWR - 10,000 lbs.
Over All Length - appox. 154 in.
Over All Width - 102 in.
Reel Capacity - 10 ft. x 60 in.
Empty Weight - 2,300 lbs.
RUNNING GEAR
Axle - 10,000 lbs.
Brakes - Electric
Tires - 215/75R17.5 LRH
Wheels - 17.5 x 6.75 8 Bolt White mod
FRAME
Main Frame - 4 x 6 in. Rectangular tube
Gun Rack Shell - 4 x 4 in. Square tube
Gun Rack Support - 3 1/2 x 3 1/2 in. Square tube
Gun Rack - 3/4 in x 5 1/2 in. flat
Tongue - 4 x 6 in. Rectangular tube
Light Boxes - 4 x 6 in. Rectangular tube
Fenders - 12 in. Jr Channel
SPINDLE BAR
Material - 2 1/2 in Diam. CRR
Auto-Locking - 1/2" Locking Plates
ELECTRICAL
Plug - 7 RV molded plug
Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped
Lights - Standard LED package
SAFETY
Chains - Rated to match
Break Away - Battery, battery box, and switch
Decals - Warning decals & reflective tape
ACCESSORIES
Wheel Chocks - Rumber
Jack - Single 12K spring loaded drop leg
FINISH
PPG Paint - Industrial urethane- White, Black, Orange, Yel.

HYDRAULICS
Cylinders - 2 x 20 in. welded
Pump - 13HP Honda motor
Valve - 3 Spool Hydraulic Motor - Eaton 22.6 CID - 3598 inch pounds of torque
Hydraulic Motor - Eaton 22.6 CID - 3598 Inch pounds of torque
ATIONAL ASSOCIATION ATIONAL ASSOCIATIONALI ATIONALI ATIONALI ATIONALI ATIONALI ATIONALI ATIONALI ATIONALI ATIONALI ATIONALI AT