



LRF 1014

SPECIFICATIONS

DESCRIPTION

MODEL - LRF 1014

GAWR - 14,000 lbs.

Over All Length - approx. 175 in.

Over All Width - 102 in.

Reel Capacity - 10 ft. x 60 in.

Empty Weight - 3,300 lbs. (Approximate)

RUNNING GEAR

Axle - 7,000 lb. Dexter Torsions

Brakes - Electric

Single Tires - 4) ST235/85R16 Load Range (E)

Wheels - 16 x 6 Silver Mod

FRAME

Main Frame - 2 x 6 in. Rectangular tube

Lift Arms - 3 x 5 in. Rectangular tube

A-Frame Tongue - 2 x 6 in. Rectangular tube

Cross Members - 3 in. Channel

Fenders - 10" Junior Channel

SPINDLE BAR

Material - 2 1/2" CRR

Spindle Bar Support - 3/8" Plates

ELECTRICAL

Plug - 7 Way Molded Plug

Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

ACCESSORIES

Wheel Chocks - Rumber

Jack - Single 12K side wind drop leg jack

FINISH

PPG Paint - Industrial urethane - White, Black, Yellow, Or

HYDRAULICS

Cylinders - 3.5 x 36 in.

Pump - Honda GX630 motor

Wireless Valves - with manual overrides

Hydraulic Motor - Eaton 2 speed hydraulic motor

LANE LRF REMOTE PENDANT

