



LRG 1010F

SPECIFICATIONS

DESCRIPTION

MODEL - LRG 1010F

GAWR - 9,995 lbs.

Over All Length - approx.. 154 in.

Over All Width - 102 in.

Reel Capacity - 120 in. Diameter x 60 in. Wide

Empty Weight - 2,500 lbs.

RUNNING GEAR

Axle - 10,000 lbs.

Brakes - Electric

Tires - 2) ST215/75R17.5 Load Range (H)

Wheels - 17.5 x 6.75 8 Bolt White mod

FRAME

Main Frame - 4 x 6 in. Rectangular tube

Gun Rack Shell - 4 x 4 in. Square tube

Gun Rack Support - 3 1/2 x 3 1/2 in. Square tube

Gun Rack - 3/4 in x 5 1/2 in. flat

Tongue - 4 x 6 in. Rectangular tube

Light Boxes - 4 x 6 in. Rectangular tube

Fenders - 12 in. Jr Channel

SPINDLE BAR

Material - 2 1/2 in Diam. CRR

Auto-Locking - 1/2" Locking Plates

ELECTRICAL

Plug - 7 Way Molded Plug

Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, and switch

Decals - Warning decals & reflective tape

ACCESSORIES

Wheel Chocks - Rubber

Jack - Single 12K spring loaded drop leg

FINISH

PPG Paint - Industrial urethane - White, Black, Yellow, Or

HYDRAULICS

Lift Cylinders - 2 x 20 in. welded

Retriever Cylinder - 2 x 10 in. Cross tube rod

Pump - 13 HP Honda motor with electric start

Custom Valving - Wireless Pendant with Manual Overrides

Retriever Motor - Eaton 8.9 CID - 2,650 inch pounds of torque

Figure 8 Motor - Eaton 8.9 CID - 2,650 inch pounds of torque

