



LPT 5050

SPECIFICATIONS

DESCRIPTION

MODEL - LPT 5050

GVWR - 45,000 lbs.

Length Retracted - approx.. 50 ft.

Length Extended - approx.. 100 ft.

Over All Width - 102 in.

Empty Weight - 18,000 lbs. (Approximate)

RUNNING GEAR

Axle - 2) 22,500 lb.

Brakes - Air

Dual Tires - 8) 11R22.5 Tires

Wheels - 275 MM

Suspension - Slipper leaf spring

FRAME

Tongues - 14 x 6 x 3/8 in. Rectangular tube

Tongue Supports - 16 x 8 x 3/8 in. Rectangular tube

Bumper - 4 x 10 in. Rectangular tube

Fenders - 10 GA. Formed

Braces - 1 1/2 in. Square tube

Cross Members - 14 x 6 x 3/8 in. Rectangular tube

ELECTRICAL

Plug - 7 Pin Round

Wiring - Enclosed in conduit w/ junction boxes
- connections soldered & shrink wrapped

Lights - Standard LED package

SAFETY

Chains - Rated to match

Break Away - Battery, battery box, solar panel, and switch

ACCESSORIES

Dual Jacks - 2 Speed 25K jacks

Winch bars - Quantity 2

Wheel Chocks - Rubber

Light Bar - Aluminum with strap

FINISH

PPG Paint - Industrial urethane- White, Black, Orange, Yel.

BOLSTERS

Material - 6" Channel

Retainers - 2 1/2" Square Tube

Tiedowns - 10) 4 in. x 27 ft. tie down straps

